

**LP2250 features:**

- “Dial in” desired power from 20% - 100%
- Adjustable air agitation ensures even temperature and reagent dispersion for all specimens
- Stainless steel interior & exterior for easy maintenance, long life
- Preset & variable time entry
- Digital countdown timer, accurate to 1 second

Includes:

- 8' Ventilation Hose
- User's Manual
- Microwave Companion

All our microwaves feature:

- High-performance vent system with standard 4” output; connect to fume hood or vent stack
- Microwave stirrers (no carousel necessary) for even microwave distribution, no “hot spots”
- “User friendly” controls, icon-based functions
- Tall chambers, for tall containers and vessels
- Illuminated interiors with stain-resistant ceramic floors
- One year parts & labor warranty
- USA manufacture; FCC compliance
- Also: help meet CAP ANP.29430, OSHA 29CFR 1910.303(b)(2), NCCLS GP28-P guidelines

Specifications:

- Exterior dimensions: 22"w x 13.5"h x 23 9/16"d
- Interior dimensions: 14.5"w x 9.25"h x 14.5"d
- Weight: 70 lbs.
- Power output: 500W
- Input power: 15A at 120v nominal
- Vent system output: 100cfm
- Presets available: 40
- Number of power settings: Full scale variable power (0-100%)