

SAFETY DATA SHEET

29B Kripes Rd, E. Granby, CT 06026

Product Information: 800.922.9037 **Emergency Assistance:(CHEMTEL, INC.)**

1.888.255.3924 (USA) +1.813.248.0573 (INT)

Version 1

Revision Date 26-Jan-2015

1. Identification

Product Name Clarifier I

LPCLAR Cat No.:

No information available **Synonyms**

Recommended Use In vitro diagnostic.

Uses advised against No Information available

Details of the supplier of the safety data sheet

Company LabPulse Medical

> 29B Kripes Road East Granby, CT 06026

Telephone (General) 800-922-9037

CHEMTEL: 1.888.255.3924 (USA) / +1.813.248.0573 (International) **Emergency Telephone**

2. Hazard(s) identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids Category 1 Acute oral toxicity Category 4 Acute Inhalation Toxicity - Vapors Category 4 Skin Corrosion/irritation Category 1 A Serious Eye Damage/Eye Irritation Category 1 Specific target organ toxicity (single exposure) Category 1 Target Organs - Central nervous system (CNS), Optic nerve. Category 1

Specific target organ toxicity - (repeated exposure)

Target Organs - Kidney, Liver, spleen, Blood.

Label Elements

Signal Word

Danger

Hazard Statements

Extremely flammable liquid and vapor Harmful if swallowed Causes severe skin burns and eye damage Harmful if inhaled May cause drowsiness or dizziness Causes damage to organs

Causes damage to organs through prolonged or repeated exposure



Precautionary Statements

Prevention

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Use only outdoors or in a well-ventilated area

Do not breathe dust/fume/gas/mist/vapors/spray

Wear protective gloves/protective clothing/eye protection/face protection

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting/equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Keep cool

Response

Immediately call a POISON CENTER or doctor/physician

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

Eves

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing **Ingestion**

Rinse mouth

Do NOT induce vomiting

Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other hazards

Poison, may be fatal or cause blindness if swallowed. Vapor harmful. Cannot be made non-poisonous. WARNING! This product contains a chemical known in the State of California to cause birth defects or other reproductive harm.

3. Composition / information on ingredients

| Component | CAS-No | Weight % |
|-------------------|-----------|----------|
| Isopropyl alcohol | 67-63-0 | 4 - 5 |
| Ethyl alcohol | 64-17-5 | 70 - 76 |
| Methyl alcohol | 67-56-1 | 4 - 5 |
| Acetic acid | 64-19-7 | 5 - 9.9 |
| Water | 7732-18-5 | 5 - 10 |

4. First-aid measures

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Immediate medical attention is required.

Skin Contact Wash off immediately with plenty of water for at least 15 minutes. Immediate medical

attention is required.

Inhalation Move to fresh air. If not breathing, give artificial respiration. Do not use mouth-to-mouth

resuscitation if victim ingested or inhaled the substance; induce artificial respiration with a

respiratory medical device. Immediate medical attention is required.

Ingestion Call a physician or Poison Control Center immediately. Do not induce vomiting.

Most important symptoms/effects Breathing difficulties. Causes burns by all exposure routes. Inhalation of high vapor

concentrations may cause symptoms like headache, dizziness, tiredness, nausea and

vomiting: Product is a corrosive material. Use of gastric lavage or emesis is

contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of

perforation

Notes to Physician Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. Use water spray to

cool unopened containers.

Unsuitable Extinguishing Media No information available

Flash Point 20.6 °C / 69.1 °F

Method - No information available

Autoignition Temperature

Explosion Limits

No information available

Upper No data available
Lower No data available
Sensitivity to Mechanical Impact No information available
Sensitivity to Static Discharge No information available

Specific Hazards Arising from the Chemical

Flammable. Risk of ignition. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back. Containers may explode when heated.

Hazardous Combustion Products

Carbon monoxide (CO) Carbon dioxide (CO₂) Thermal decomposition can lead to release of irritating gases and vapors **Protective Equipment and Precautions for Firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

NFPA

HealthFlammabilityInstabilityPhysical hazards340N/A

6. Accidental release measures

Personal Precautions Use personal protective equipment. Remove all sources of ignition. Take precautionary

measures against static discharges. Do not get in eyes, on skin, or on clothing.

Environmental Precautions Should not be released into the environment. See Section 12 for additional ecological

information.

Methods for Containment and Clean Remove all sources of ignition. Soak up with inert absorbent material. Take precautionary

Up measures against static discharges. Keep in suitable, closed containers for disposal.

7. Handling and storage

Handling Use only under a chemical fume hood. Wear personal protective equipment. Use

explosion-proof equipment. Use only non-sparking tools. Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharges.

Do not breathe vapors or spray mist. Do not get in eyes, on skin, or on clothing.

Storage Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat

and sources of ignition. Flammables area.

8. Exposure controls / personal protection

Exposure Guidelines

| Component | ACGIH TLV | OSHA PEL | NIOSH IDLH |
|-------------------|--|--|---|
| Isopropyl alcohol | TWA: 200 ppm STEL: 400 ppm (Vacated) TWA: 400 ppm (Vacated) STEL: 500 ppm (Vacated) STEL: 1225 mg/m³ TWA: 400 ppm TWA: 980 mg/m³ | | IDLH: 2000 ppm TWA: 400 ppm TWA: 980 mg/m³ STEL: 500 ppm STEL: 1225 mg/m³ |
| Ethyl alcohol | STEL: 1000 ppm | (Vacated) TWA: 1000 ppm (Vacated) TWA: 1900 mg/m³ TWA: 1000 ppm TWA: 1900 mg/m³ | IDLH: 3300 ppm TWA: 1000 ppm TWA: 1900 mg/m³ |
| Methyl alcohol | TWA: 200 ppm STEL: 250 ppm Skin | (Vacated) TWA: 200 ppm (Vacated) TWA: 260 mg/m³ (Vacated) STEL: 250 ppm (Vacated) STEL: 325 mg/m³ Skin TWA: 200 ppm TWA: 260 mg/m³ | IDLH: 6000 ppm TWA: 200 ppm TWA: 260 mg/m³ STEL: 250 ppm STEL: 325 mg/m³ |
| Acetic acid | TWA: 10 ppm STEL: 15 ppm | (Vacated) TWA: 10 ppm (Vacated) TWA: 25 mg/m³ TWA: 10 ppm TWA: 25 mg/m³ | IDLH: 50 ppm TWA: 10 ppm TWA: 25 mg/m³ STEL: 15 ppm STEL: 37 mg/m³ |

| Component | Quebec | Mexico OEL (TWA) | Ontario TWAEV |
|-------------------|--|---|---------------------------------------|
| Isopropyl alcohol | TWA: 400 ppm TWA: 985 mg/m³ STEL: 500 ppm STEL: 1230 mg/m³ | TWA: 400 ppm TWA: 980 mg/m³ STEL: 500 ppm STEL: 1225 mg/m³ | TWA: 200 ppm STEL: 400 ppm |
| Ethyl alcohol | TWA: 1000 ppm TWA: 1880 mg/m ³ | TWA: 1000 ppm TWA: 1900 mg/m ³ | STEL: 1000 ppm |
| Methyl alcohol | TWA: 200 ppm TWA: 262 mg/m³ STEL: 250 ppm STEL: 328 mg/m³ Skin | TWA: 200 ppm TWA: 260 mg/m³ STEL: 250 ppm STEL: 310 mg/m³ | TWA: 200 ppm STEL: 250 ppm Skin |
| Acetic acid | TWA: 10 ppm TWA: 25 mg/m³ STEL: 15 ppm STEL: 37 mg/m³ | TWA: 10 ppm TWA: 25 mg/m³ STEL: 15 ppm STEL: 37 mg/m³ | TWA: 10 ppm STEL: 15 ppm |

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH IDLH: The National Institute for Occupational Safety and Health Immediately Dangerous to Life or Health

Engineering Measures Use only under a chemical fume hood. Use explosion-proof

electrical/ventilating/lighting/equipment. Ensure that eyewash stations and safety showers

are close to the workstation location.

Personal Protective Equipment

Eye/face Protection Wear appropriate protective eyeglasses or chemical safety goggles as described by

OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard

EN166.

Skin and body protectionWear appropriate protective gloves and clothing to prevent skin exposure.

Respiratory Protection Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard

EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Physical StateLiquidAppearanceClearOdoraromatic

Odor Threshold
pH

No information available
No information available

Melting Point/Range No data available

Boiling Point/Range

Flash Point

Evaporation Rate

No information available
20.6 °C / 69.1 °F

No information available
No information available
No information available

Flammability (solid,gas)
Flammability or explosive limits

UpperNo data availableLowerNo data available

Vapor PressureNo information availableVapor DensityNo information availableRelative DensityNo information available

Solubility

Partition coefficient; n-octanol/water

Autoignition Temperature

Decomposition Temperature

Soluble in water

No data available

No information available

No information available

Viscosity No information available

10. Stability and reactivity

Reactive Hazard None known, based on information available

Stability Stable under normal conditions.

Conditions to Avoid Incompatible products. Heat, flames and sparks.

Incompatible Materials Strong oxidizing agents, Acids, Acid anhydrides, Acid chlorides

Hazardous Decomposition Products Carbon monoxide (CO₂), Carbon dioxide (CO₂), Thermal decomposition can lead to release

of irritating gases and vapors

Hazardous Polymerization Hazardous polymerization does not occur.

Hazardous Reactions None under normal processing.

11. Toxicological information

Acute Toxicity

Product InformationNo acute toxicity information is available for this product

Oral LD50 Category 4. ATE = 300 - 2000 mg/kg.

Dermal LD50Based on ATE data, the classification criteria are not met. ATE > 2000 mg/kg.

Vapor LC50 Category 4. ATE = 10 - 20 mg/l.

Component Information

| Component | LD50 Oral | LD50 Dermal | LC50 Inhalation |
|-------------------|--------------------|---|--|
| Isopropyl alcohol | 5840 mg/kg (Rat) | 13900 mg/kg (Rat) 12870 mg/kg (Rabbit) | 72.6 mg/L (Rat) 4 h |
| Ethyl alcohol | 7060 mg/kg (Rat) | Not listed | 20000 ppm/10H (Rat) |
| Methyl alcohol | 6200 mg/kg (Rat) | 15800 mg/kg (Rabbit) | 64000 ppm (Rat) 4 h 22500 ppm (Rat) 8 h |
| Acetic acid | 3310 mg/kg (Rat) | 1060 mg/kg (Rabbit) | 11.4 mg/L (Rat)4 h |

Toxicologically Synergistic

Products

No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation Severe eye irritant

Sensitization No information available

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

| Component | CAS-No | IARC | NTP | ACGIH | OSHA | Mexico |
|-------------------|-----------|------------|------------|------------|------------|------------|
| Isopropyl alcohol | 67-63-0 | Not listed |
| Ethyl alcohol | 64-17-5 | Group 1 | Not listed | A3 | X | Not listed |
| Methyl alcohol | 67-56-1 | Not listed |
| Acetic acid | 64-19-7 | Not listed |
| Water | 7732-18-5 | Not listed |

IARC: (International Agency for Research on Cancer)

IARC: (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2A - Probably Carcinogenic to Humans Group 2B - Possibly Carcinogenic to Humans

Mutagenic Effects Mutagenic effects have occurred in humans.

Reproductive Effects Adverse reproductive effects have occurred in humans.

Developmental EffectsSubstances known to cause developmental toxicity in humans.

Teratogenicity Teratogenic effects have occurred in humans.

STOT - single exposure Central nervous system (CNS) Optic nerve

STOT - repeated exposure Kidney Liver spleen Blood

Symptoms / effects,both acute and

delayed

Aspiration hazard

Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and

danger of perforation

No information available

No information available

Endocrine Disruptor Information No information available

Other Adverse Effects Tumorigenic effects have been reported in experimental animals. See actual entry in

RTECS for complete information.

12. Ecological information

Ecotoxicity

| Component | Freshwater Algae | Freshwater Fish | Microtox | Water Flea |
|-------------------|-----------------------|---|----------------------------------|------------------------|
| Isopropyl alcohol | 1000 mg/L EC50 > 96 h | 1400000 µg/L LC50 96 h | = 35390 mg/L EC50 | 13299 mg/L EC50 = 48 h |
| | 1000 mg/L EC50 > 72 h | 11130 mg/L LC50 96 h 9640 mg/L LC50 96 h | Photobacterium phosphoreum 5 min | 9714 mg/L EC50 = 24 h |

| Ethyl alcohol | EC50 (72h) = 275 mg/l (Chlorella vulgaris) | LC50 = 14200 mg/l/96h | Photobacterium phosphoreum:EC50 = 34634 mg/L/30 min Photobacterium phosphoreum:EC50 = 35470 mg/L/5 min | EC50 = 9268 mg/L/48h EC50 = 10800 mg/L/24h |
|----------------|---|--|--|---|
| Methyl alcohol | Not listed | Pimephales promelas: LC50 > 10000 mg/L 96h | EC50 = 39000 mg/L 25 min EC50 = 40000 mg/L 15 min EC50 = 43000 mg/L 5 min | EC50 > 10000 mg/L 24h |
| Acetic acid | - | Pimephales promelas: LC50 = 88 mg/L/96h Lepomis macrochirus: LC50 = 75 mg/L/96h | phosphoreum: EC50 = 8.8 | EC50 = 95 mg/L/24h |

Persistence and Degradability Bioaccumulation/ Accumulation

No information available No information available.

Mobility

| Component | log Pow |
|-------------------|---------|
| Isopropyl alcohol | 0.05 |
| Ethyl alcohol | -0.32 |
| Methyl alcohol | -0.74 |
| Acetic acid | -0.2 |

13. Disposal considerations

Waste Disposal Methods

Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

| Component | RCRA - U Series Wastes | RCRA - P Series Wastes |
|--------------------------|------------------------|------------------------|
| Methyl alcohol - 67-56-1 | U154 | - |

14. Transport information

DOT

UN-No UN1987

Proper Shipping Name ALCOHOLS, N.O.S. Proper technical name (Ethanol, Methanol)

Hazard Class 3 Packing Group II

TDG

UN-No UN1987

Proper Shipping Name ALCOHOLS, N.O.S.

Hazard Class 3 Packing Group II

<u>IATA</u>

UN-No UN1987

Proper Shipping Name ALCOHOLS, N.O.S.

Hazard Class 3 Packing Group II

IMDG/IMO

UN-No UN1987

Proper Shipping Name ALCOHOLS, N.O.S.

Hazard Class 3
Packing Group ||

15. Regulatory information

International Inventories

| Component | TSCA | DSL | NDSL | EINECS | ELINCS | NLP | PICCS | ENCS | AICS | IECSC | KECL |
|-------------------|------|-----|------|---------------|--------|-----|-------|------|------|-------|------|
| Isopropyl alcohol | Χ | Χ | - | 200-661-7 | - | | Χ | Χ | Χ | Χ | Χ |
| Ethyl alcohol | X | Χ | - | 200-578-6 | - | | Х | Χ | Χ | Χ | X |
| Methyl alcohol | Х | Χ | - | 200-659-6 | - | | Х | Χ | Χ | Χ | Χ |
| Acetic acid | Х | Χ | - | 200-580-7 | - | | Х | Χ | Χ | Χ | Х |
| Water | Х | Х | - | 231-791-2 | - | | Х | - | Х | Х | Х |

Legend:

- X Listed
- E Indicates a substance that is the subject of a Section 5(e) Consent order under TSCA.
- F Indicates a substance that is the subject of a Section 5(f) Rule under TSCA.
- N Indicates a polymeric substance containing no free-radical initiator in its inventory name but is considered to cover the designated polymer made with any free-radical initiator regardless of the amount used.
- P Indicates a commenced PMN substance
- R Indicates a substance that is the subject of a Section 6 risk management rule under TSCA.
- S Indicates a substance that is identified in a proposed or final Significant New Use Rule
- T Indicates a substance that is the subject of a Section 4 test rule under TSCA.
- XU Indicates a substance exempt from reporting under the Inventory Update Rule, i.e. Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(B).
- Y1 Indicates an exempt polymer that has a number-average molecular weight of 1,000 or greater.
- Y2 Indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.

U.S. Federal Regulations

TSCA 12(b)

Not applicable

SARA 313

| Component | CAS-No | Weight % | SARA 313 - Threshold Values % |
|-------------------|---------|----------|----------------------------------|
| Isopropyl alcohol | 67-63-0 | 4 - 5 | 1.0 |
| Methyl alcohol | 67-56-1 | 4 - 5 | 1.0 |

SARA 311/312 Hazardous Categorization

Yes **Acute Health Hazard Chronic Health Hazard** Yes Fire Hazard Yes **Sudden Release of Pressure Hazard** No **Reactive Hazard** No

Clean Water Act

| Component | CWA - Hazardous Substances | CWA - Reportable Quantities | CWA - Toxic Pollutants | CWA - Priority Pollutants |
|-------------|-------------------------------|--------------------------------|------------------------|---------------------------|
| Acetic acid | X | 5000 lb | - | - |

Clean Air Act

| Component | HAPS Data | Class 1 Ozone Depletors | Class 2 Ozone Depletors |
|----------------|-----------|-------------------------|-------------------------|
| Methyl alcohol | Х | | - |

OSHA Occupational Safety and Health Administration

Not applicable

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

| Component | Hazardous Substances RQs | CERCLA EHS RQs |
|----------------|--------------------------|----------------|
| Methyl alcohol | 5000 lb | |
| Acetic acid | 5000 lb | |

California Proposition 65

This product contains the following Proposition 65 chemicals: Ethyl alcohol is only a considered a Proposition 65 developmental hazard when it is ingested as an alcoholic beverage

| Component | CAS-No | California Prop. 65 | Prop 65 NSRL | Category |
|----------------|---------|---------------------|--------------|-----------------------------|
| Ethyl alcohol | 64-17-5 | Developmental | - | Developmental Carcinogen |
| Methyl alcohol | 67-56-1 | Developmental | - | Developmental |

State Right-to-Know

| Component | Massachusetts | New Jersey | Pennsylvania | Illinois | Rhode Island |
|-------------------|---------------|------------|--------------|----------|--------------|
| Isopropyl alcohol | X | X | X | - | X |
| Ethyl alcohol | X | X | X | X | X |
| Methyl alcohol | X | X | X | X | X |
| Acetic acid | X | X | X | - | X |
| Water | - | - | X | - | - |

U.S. Department of Transportation

Reportable Quantity (RQ): Y
DOT Marine Pollutant N
DOT Severe Marine Pollutant N

U.S. Department of Homeland Security

This product does not contain any DHS chemicals.

Other International Regulations

Mexico - Grade No information available

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR

WHMIS Hazard Class B2 Flammable liquid

D1B Toxic materials D2A Very toxic materials E Corrosive material



16. Other information

Revision Date 26-Jan-2015

Disclaimer

Labpulse Medical makes no representation as to the comprehensiveness or accuracy of this document. Individuals using this information, or the product to which it refers, must exercise their independent judgment in determining all appropriateness for a particular purpose. Accordingly, Labpulse Medical will not be responsible for damages of any kind or nature resulting from the use of this information or the corresponding product. No representations or warranties of any kind or nature, including but not limited to: express warranties, implied warranties or merchantability, or warranties of fitness for a particular purpose, are made hereunder with respect to the information set forth herein or to the product to which the information refers.

End of Safety Data Sheet